

TECNOVE

FIBERGLASS



Technical Specifications

Standard equipment

- Exterior door handle
- Tool box
- Mudguard
- Normal stainless steel fittings
- 3mm stainless steel rear framework
- Two rear doors
- Antislip tailgate
- Light
- Siphon
- Block
- Pultruded body protection mouldings

Optional equipment

- Thermal curtain
- Small deflector
- Stainless steel recess
- Folding ladder
- Extension ladder
- Ventilation hatch
- Load securing guide
- Floor mounted guides
- TIR type fittings
- TIR type framework
- LED pilot light
- Aluminium floor
- Plasticised tile floor
- Side underrun guard
- Rear door
- Side doors
- Interior opening system
- Divider panel system
- Shelving
- Fitted step
- Tail lift
- Cooling equipment
- Meat carrier reinforcements
- Meat carrier bars.

Up to 3.500Kg

MODEL THICKNESSES




PANEL	THICKNESS
Floor	101
Ceiling	86
Doors	86
Sides	61
Front	61

MODELS DIMENSIONS

Dimension	Min. -Max.
Length	1500-4500
Width	1750-2350
Height	1750-2300

MODEL CAPACITY

Up to 8 pallets



TECNOVE

FIBERGLASS

Up to 3.500Kg

